



320 amp Single Phase UG Pedestals

Milbank	U1748-0-WI	ext. S1848
Square D	1009018-SQD	ext. 1009023-SQD (18") or 1009026-SQD (30")
Cutler Hammer	1009018-CH	ext. 1009023-CH (18") or 1009026-CH (30")
Midwest	1009018-MEP	ext. 1009023-MEP (18") or 1009026-MEP (30")
Durham	1009018	ext. 1009023 (18") or 1009026 (30")
Landis & Gyr	47604P-9WI	
Square D (Anchor)	MP443242-WI	

320 amp Single Phase UG Pedestal with Two 200 amp Mains

Durham	1009017	ext. 1009022 (18") or 1009025 (30")
Cutler Hammer	1009017-CH	ext. 1009022-CH (18") or 1009025-CH (30")
Milbank	U3849-0-INV	(no extension available)

NOTES:

1. This is a 320 class meter. Designed for 320 Amps continuous and 400 amps intermittent. The above are possible acceptable catalog numbers. Need one extension for UPPCo. Extensions only needed in WPSC if required for height reasons.
2. 320 amp meter sockets are acceptable for OH and multiple UG installations, if UL listed, ringless, have a bypass lever, are capable of terminating 350 KCM Al conductor, and have no cover over the meter.

Revised: 03/10

WPSC/UPPCO SERVICE MANUAL

320 CLASS / 400 AMP SINGLE PHASE UG